



SOLRIF D


series

Agro


 **300 W**

 **Made in the EU**


3.2+3.2 mm glass



Ammonia
resistance



Extreme load
resistance



98 %
recyclable



Hail resistance
class 5



35% of recycled
glass content

30 **Product &
Efficiency
Guarantee**
YEAR

90%
POWER WARRANTY



Electrical data	STC*	BNPI**
Maximum power (W)	300	330
Cell technology	N type, TOPCon - bifacial	
Open circuit voltage (V_{oc}/V)	23,30	23,30
Short circuit current (I_{sc}/A)	15,97	17,57
Max power voltage (V_{mpp}/V)	19,60	
Max power current (I_{mpp}/A)	15,31	
Module efficiency (η)	14,87 %	
Max system voltage (V)	1500	
Max current (A)	30	
Power tolerance	0/+5W	


*Under standard test conditions (STC) of irradiance of 1000W/sq.m., spectrum AM 1.5 and cell temperature of 25°C. Flash testing measurement accuracy of +/-5%.
**BNPI: front 1000W/m², rear 135W/m²

Warranty

30 years product warranty

30 years efficiency warranty

First year degradation (%)	1
Annual degradation (%)	0,31
Power in year 30 (%)	90



Certifications

IEC 61215:2021; IEC 61730:2023	
C2C Certified®***	Full Scope, Silver level, Version 4.1
IEC 62716:2013	Ammonia corrosion testing
EN 13501-5	Broof (t1)
IEC 61701:2020	Salt mist corrosion testing
IEC 61215-2:2021	50 mm hailstone - Hail resistance class 5 (HW5)
ISO 9001:2015	Quality management systems
ISO 14001:2015	Environmental management systems
ISO 45001:2018	Occupational health and safety
SundaHus	A level assessment
Produced using 100% renewable energy	
Membership at Svensk Solenergi	



Packing information

Modules per pallet (pcs)	25
Dimensions of a pallet (LxWxH) (mm)	1899x1203x1070
Weight of a pallet (gross) (kg)	1040
Pallets per 13,6 m truck (pcs)	23
Modules per 13,6 m truck (pcs)	575


*** - the certification scope is limited to the laminate and does not include the frames

Temperature ratings


Current temperature coefficient (α)	+0,0371% / °C
Voltage temperature coefficient (β)	-0,2173% / °C
Power temperature coefficient (δ)	-0,2791% / °C
Nominal operating module temperature	46 °C

Mechanical data

Dimensions (LxWxH) (mm)	1806x1160x20
Grid dimensions (LxW) (mm)	1788x1128
Weight (kg)	35
Front glass (mm)	3,2, structured, low reflection, with AR coating, TVG
Back glass (mm)	3,2, transparent, TVG
Cell Size (mm)	182,2x105
Busbars	16
Cell configuration	4x16
Frame	Solrif D
Rated operating altitude (m)	Up to 2000
Operating temperature (°C)	-40 ÷ +85
Maximum test load (wind/snow) (Pa)	3600/10500
Junction box / IP class	Split junction box / IP68
Cable cross section size (mm²)	4
Cable length (m)	1,2
Bypass diodes	3
Connector	MC4-EVO2



Performance at Low Irradiance



This datasheet is not legally binding. The manufacturer reserves the right to make changes to product specifications and / or product features without prior notice. The most recent versions of all documents (T&C's, datasheets, warranties and installation manuals) can always be found on our website at www.solitek.eu

The manufacturer of the system, Ernst Schweizer AG, provides a 10 year warranty on materials supplied for the Solrif roof integrated PV mounting system. The warranty agreement of Ernst Schweizer AG does not refer to the solar modules and the terms of warranty of Soli Tek cells UAB.

QRious?



Scan to learn more